

CELEBRATING
28th
 YEARS
 ANNIVERSARY



VASANI
 POLYMERS PVT. LTD.

Delivering Pipes,
 Building Trust

Solvent Cement



Vasani Polymers Pvt. Ltd.

Manufacturing Unit

Survey No 488/p & 519/p GIDC Talod - 383215,
 Dist: Sabarkantha, Gujarat, India.

Corporate Office

D/604, Ganesh Meridian, Opp. Gujarat High Court,
 S.G. Highway, Sola, Ahmedabad, Gujarat, India - 380060

info@vasanipolymers.com | sales@vasanipolymers.com

Customer Care : +91-9409309800

www.vasanipolymers.com



Solvent Cement



AGRI PVC SOLVENT CEMENT:

PRODUCT BRIEF :

- Packing:
Tube: 10,25,50 ml
Tin Can: 100, 250, 500, 1000, 5000 ml
- Color: Clear | High Pressure - ISI Approved
- Store product below 44°C (111°F).
- Compliance with ISI - IS14182 standard.
- Brookfield Viscosity : Min. 90 cP.

APPLICATION :

- Specially formulated for all types of ISI PVC irrigation piping systems.
- It can be used for conduit, sewer, drain, waste and vent systems.

ADVANTAGE :

- Regular bodied, slow setting, HIGH PRESSURE, high strength cement.
- It provides long working time to make joints in a hot climate.
- Shelf life:
Tin Can & Tube: 2 years
HDPE Can: 1 year

UPVC SOLVENT CEMENT:

PRODUCT BRIEF :

- Packing:
Tube: 10,25,59 ml
Tin Can: 118,237,473 ml"
- Color: Clear | Blue | Heavy Duty - Low VOC
- Designed for all grades and types of PVC, UPVC (PVC-U) pipe and fittings through 6" (152mm) diameter Schedule 40 & 4" (101mm) diameter Schedule 80 interference fit, PVC-U PN10 & 16.
- Certified by NSF International for compliance with NSF/ANSI 14, NSF/ANSI 61 & ASTM D-2564.
- Meets SCAQMD Rule 1168/316A and Qualify for LEED® Green Building requirements.
- Brookfield Viscosity: Minimum 500 cP.
- Store product below 44°C (111°F).

APPLICATION :

- For potable water, plumbing, irrigation, conduit, sewer, drain, waste and vent systems.
- Primer is strongly recommended for pipe diameter > 3" (76mm).

ADVANTAGE :

- Medium bodied, fast setting, high strength Low VOC solvent cement.
- Shelf life:
Tin Can & Tube: 3 years

CPVC SOLVENT CEMENT:

PRODUCT BRIEF :

- Packing:
Tube: 10,25,59 ml
Tin Can: 118,237,473 ml"
- Color: Yellow | Medium Bodied - Low VOC
- Designed for all grades and types of CPVC pipe and fittings through 4" (101mm) diameter schedule 40 & schedule 80 interference fit and SDR 13.5 & 11.
- Certified by NSF International for compliance with NSF/ANSI 14, NSF/ANSI 61, ASTM F-493 & ASTM D-2846.
- Meets SCAQMD Rule 1168/316A and Qualify for LEED® Green Building requirements.
- Brookfield Viscosity: Minimum 500 cP.
Store product below 33°C (90°F).

APPLICATION :

- For hot & cold potable water up to 82°C (180°F)

ADVANTAGE :

- Medium bodied, fast setting, high strength Low VOC CPVC solvent cement.
- Shelf life:
Tin Can & Tube: 2 years